

## VEHICLE WASH

### For Pressure Washing of Vehicles

#### DIRECTIONS:

- Drop two Packs of Vehicle Wash into the pre-labeled 5 gallon pail. Add 3-5 gallons of water and allow the Pack to dissolve.
  - In colder temperatures, it may take a little longer to dissolve.
- Insert power washer pick-up tube into pail.
- Cover vehicle with detergent using the power washer nozzle set on soap dispensing setting.
- The product is designed to have a lower level of foam, but when using a power washer it should foam well.
  - The amount of product that is pulled into the system - or dilution ratio - will vary depending on the brand of the power washer. In some cases, the dilution ratio can be changed using an adjustment screw on the equipment. Adjust the dilution ratio until the desired level of foam is reached.
  - If there is no adjustment screw, add or subtract the number of Packs used to determine the effect on concentration.
- Scrub vehicle as needed with an approved brush.
- Rinse car completely on high pressure.



#### Technical Data

Pack Size: 20 Grams  
Yield per Pack: 3-5 Gallon  
Solubility in Water: Complete  
pH at Use Dilution: 6.5-8.5  
Color: Pink  
Fragrance: Pleasant  
Phosphates: None

#### Overview

The product is designed to help sheet the water off the car. This is done by adding a rinse aid and a binding agent to the formulation that reduces the water's surface tension on the vehicle, allowing it to sheet off the car reducing drying time and water spots.

- Do not handle Packs with wet hands.
- Do not remove Packs from container prior to use.
- Do not expose Packs to subzero temperatures.
- Do not cut Packs open. The Pack is 100% soluble in water.

Emergency Response #: 1-800-535-5053

Reorder at [www.shoplonghouse.com](http://www.shoplonghouse.com)  
50/tub: 4-2125

Dist. by:

**Longhouse Inventory Solutions, LLC**  
21052 S. 4175 Rd. • Claremore, OK 74019 • 918.342.3127  
[www.shoplonghouse.com](http://www.shoplonghouse.com) • Mfd. by ACP

